

EXHIBIT D

```
0 /* *****
1   File: ciphers.c
2
3   SSL Plus: Security Integration Suite(tm)
4   Version 1.1.1 -- August 11, 1997
5
6   Copyright (c)1996, 1997 by Consensus Development Corporation
7   Copyright (c)1997, 1998 by Aventail Corporation
8
9   Portions of this software are based on SSLRef(tm) 3.0, which is
10  Copyright (c)1996 by Netscape Communications Corporation. SSLRef(tm)
11  was developed by Netscape Communications Corporation and Consensus
12  Development Corporation.
13
14  In order to obtain this software, your company must have signed
15  either a PRODUCT EVALUATION LICENSE (a copy of which is included in
16  the file "LICENSE.TXT"), or a PRODUCT DEVELOPMENT LICENSE. These
17  licenses have different limitations regarding how you are allowed to
18  use the software. Before retrieving (or using) this software, you
19  *must* ascertain which of these licenses your company currently
20  holds. Then, by retrieving (or using) this software you agree to
21  abide by the particular terms of that license. If you do not agree
22  to abide by the particular terms of that license, then you must
23  immediately delete this software. If your company does not have a
24  signed license of either kind, then you must either contact
25  Consensus Development and execute a valid license before retrieving
26  (or using) this software, or immediately delete this software.
27
28  *****
29
30  File: ciphers.c    Data structures for handling supported ciphers
31
32  Contains a table mapping cipherSuite values to the ciphers, MAC
33  algorithms, key exchange procedures and so on that are used for that
34  algorithm, in order of preference.
35
36  ***** */
37
38 #ifndef _CRYPTYPE_H_
39 #include <crypttype.h>
40 #endif
41
42 #ifndef _SSLCTX_H_
43 #include <sslctx.h>
44 #endif
45
46 #include <string.h>
47
48 extern SSLSymmetricCipher SSLCipherNull;
49 extern SSLSymmetricCipher SSLCipherDES_CBC;
50 extern SSLSymmetricCipher SSLCipherDES40_CBC;
51 extern SSLSymmetricCipher SSLCipherRC4_40;
52 extern SSLSymmetricCipher SSLCipherRC4_56;
53 extern SSLSymmetricCipher SSLCipherRC4_128;
54 extern SSLSymmetricCipher SSLCipher3DES_CBC;
55
56 /* Even if we don't support NULL_WITH_NULL_NULL for transport, we need a reference for startup
57 */
58 SSLCipherSpec SSL_NULL_WITH_NULL_NULL_CipherSpec =
59 {
60     SSL_NULL_WITH_NULL_NULL,
61     Exportable,
62     SSL_NULL_auth,
63     &SSLHashNullOpt,
64     &SSLCipherNull
65 };
66
67 /* Disable non-exportable cipher suites to build an export only library */
68 #ifndef ENABLE_NONEXPORT_CIPHERS
69 #define ENABLE_NONEXPORT_CIPHERS 1
70 #endif
71
```

```
70 /* Disable exportable cipher suites to build a strong crypto only library */
71 #ifndef ENABLE_EXPORT_CIPHERS
72 #define ENABLE_EXPORT_CIPHERS 1
73 #endif
74
75 /* Reenable DH-anon only if you know you want to use Diffie-Hellman cipher suites:
76    Enabling DH-anon leaves you open to a man-in-the-middle attack which can degrade your
77    security to this level. */
78 #ifndef ENABLE_DH_ANON
79 #define ENABLE_DH_ANON 0
80 #endif
81
82 /* Reenable NULL encryption cipher suites only if you know for a fact you want to support
83    unencrypted sessions. Unencrypted sessions do not provide data privacy and may be more
84    vulnerable to attack than encrypted sessions. */
85 #ifndef ENABLE_NULL_CIPHERS
86 #define ENABLE_NULL_CIPHERS 0
87 #endif
88
89 #ifdef VIRGIN_SSLPLUS
90 /* Order by preference */
91 SSLCipherSpec KnownCipherSpecs[] =
92 {
93     #if ENABLE_NONEXPORT_CIPHERS
94     { SSL_RSA_WITH_3DES_EDE_CBC_SHA, NotExportable, SSL_RSA, &SSLHashSHA1, &SSLCipher3DES_CBC },
95     { SSL_RSA_WITH_RC4_128_SHA, NotExportable, SSL_RSA, &SSLHashSHA1, &SSLCipherRC4_128 },
96     { SSL_RSA_WITH_RC4_128_MD5, NotExportable, SSL_RSA, &SSLHashMD5, &SSLCipherRC4_128 },
97     { SSL_RSA_WITH_DES_CBC_SHA, NotExportable, SSL_RSA, &SSLHashSHA1, &SSLCipherDES_CBC },
98     #endif
99     #if ENABLE_EXPORT_CIPHERS
100     { SSL_RSA_EXPORT_WITH_RC4_40_MD5, Exportable, SSL_RSA_EXPORT, &SSLHashMD5,
      &SSLCipherRC4_40 },
101     { SSL_RSA_EXPORT_WITH_DES40_CBC_SHA, Exportable, SSL_RSA_EXPORT, &SSLHashSHA1,
      &SSLCipherDES40_CBC },
102     #endif
103     #if ENABLE_DH_ANON && ENABLE_NONEXPORT_CIPHERS
104     { SSL_DH_anon_WITH_3DES_EDE_CBC_SHA, NotExportable, SSL_DH_anon, &SSLHashSHA1,
      &SSLCipher3DES_CBC },
105     { SSL_DH_anon_WITH_RC4_128_MD5, NotExportable, SSL_DH_anon, &SSLHashMD5,
      &SSLCipherRC4_128 },
106     { SSL_DH_anon_WITH_DES_CBC_SHA, NotExportable, SSL_DH_anon, &SSLHashSHA1,
      &SSLCipherDES_CBC },
107     #endif
108     #if ENABLE_NULL_CIPHERS && ENABLE_EXPORT_CIPHERS
109     { SSL_RSA_WITH_NULL_SHA, Exportable, SSL_RSA, &SSLHashSHA1, &SSLCipherNull },
110     { SSL_RSA_WITH_NULL_MD5, Exportable, SSL_RSA, &SSLHashMD5, &SSLCipherNull },
111     #endif
112 };
113
114 int CipherSpecCount = sizeof(KnownCipherSpecs) / sizeof(SSLCipherSpec);
115 #endif /* VIRGIN_SSLPLUS */
116
117 SSLerr
118 FindCipherSpec(SSLContext *ctx, uint16 specID, SSLCipherSpec *spec)
119 {
120     int i;
121     uint32 mask;
122
123     *spec = 0;
124     for (i = 0; i < CipherSpecCount; i++)
125     {
126         if (KnownCipherSpecs[i].cipherSpec == specID)
127         {
128             mask = (uint32) 1;
129             mask <= i;
130             if (ctx->cipherspecs & mask)
131             {
132                 *spec = &KnownCipherSpecs[i];
133                 break;
134             }
135         }
136     }
137 }
```

```
135     )
136   )
137
138   if (*spec == 0)          /* Not found */
139     return SSLNegotiationErr;
140   return SSLNoErr;
141 }
142
143 SSLErr SSLDESInit(uint8 *key, uint8 *iv, void **cipherRef, SSLContext *ctx);
144 SSLErr SSLDESEncrypt(SSLBuffer src, SSLBuffer dest, SSLBuffer *iv, void *cipherRef, SSLContext
    *ctx);
145 SSLErr SSLDESDecrypt(SSLBuffer src, SSLBuffer dest, SSLBuffer *iv, void *cipherRef, SSLContext
    *ctx);
146 SSLErr SSLDESFinish(void *cipherRef, SSLContext *ctx);
147 SSLErr SSLDESExport(void *cipherRef, SSLContext *ctx, SSLBuffer *blob);
148 SSLErr SSLDESImport(void **cipherRef, SSLContext *ctx, SSLBuffer *blob);
149
150 SSLSymmetricCipher SSLCipherDES_CBC = {
151     8,          /* Key size in bytes */
152     8,          /* Secret key size = 64 bits */
153     8,          /* IV size */
154     8,          /* Block size */
155     SSLDESInit,
156     SSLDESEncrypt,
157     SSLDESDecrypt,
158     SSLDESFinish,
159     SSLDESExport,
160     SSLDESImport
161 };
162
163 SSLSymmetricCipher SSLCipherDES40_CBC = {
164     8,          /* Key size in bytes */
165     5,          /* Secret key size = 40 bits */
166     8,          /* IV size */
167     8,          /* Block size */
168     SSLDESInit,
169     SSLDESEncrypt,
170     SSLDESDecrypt,
171     SSLDESFinish
172 };
173
174 typedef struct _DESState
175 {
176     unsigned char key[24]; /* work for 3DES and DES both */
177     unsigned char iv[8];
178     int reading; /* do we really need this? */
179     B_ALGORITHM_OBJ des;
180 } DESState;
181
182 SSLErr
183 SSLDESInit(uint8 *key, uint8 *iv, void **cipherRef, SSLContext *ctx)
184 {
185     SSLBuffer desState;
186     B_ALGORITHM_OBJ *des;
187     static B_ALGORITHM_METHOD *chooser[] = { &AM_DES_CBC_ENCRYPT, &AM_DES_CBC_DECRYPT, 0 };
188     B_KEY_OBJ desKey;
189     ITEM keyData;
190     SSLErr err;
191     int rsaErr;
192     DESState *s;
193
194     if ((err = SSLAllocBuffer(&desState, sizeof(DESState), &ctx->sysCtx)) != 0)
195         return err;
196     s = (DESState *)desState.data;
197
198     memcpy(s->key, key, 8);
199     memcpy(s->iv, iv, 8);
200
201     if ((rsaErr = B_CreateAlgorithmObject(&(s->des))) != 0)
202         return SSLUnknownErr;
```

```
203     if ((rsaErr = B_SetAlgorithmInfo(s->des, AI_DES_CBC_IV8, iv)) != 0)
204         return SSLUnknownErr;
205     if ((rsaErr = B_CreateKeyObject(&desKey)) != 0)
206         return SSLUnknownErr;
207     keyData.data = key;
208     keyData.len = 8;
209     if ((rsaErr = B_SetKeyInfo(desKey, KI_DES8, key)) != 0)
210     {
211         B_DestroyKeyObject(&desKey);
212         return SSLUnknownErr;
213     }
214     if (cipherRef == (void*)&(ctx->writePending.symCipherState))
215     {
216         s->reading = 0;
217         if ((rsaErr = B_EncryptInit(*des, desKey, chooser, &ctx->sysCtx.yield)) != 0)
218         {
219             B_DestroyKeyObject(&desKey);
220             return SSLUnknownErr;
221         }
222     }
223     else if (cipherRef == (void*)&(ctx->readPending.symCipherState))
224     {
225         s->reading = 1;
226         if ((rsaErr = B_DecryptInit(*des, desKey, chooser, &ctx->sysCtx.yield)) != 0)
227         {
228             B_DestroyKeyObject(&desKey);
229             return SSLUnknownErr;
230         }
231     }
232     else
233         ASSERTMSG("Couldn't determine read/writeness");
234     B_DestroyKeyObject(&desKey);
235     *cipherRef = (void*)s;
236     return SSLNoErr;
237 }
238
239 SSLERR
240 SSLDESEncrypt(SSLBuffer src, SSLBuffer dest, SSLBuffer *iv, void *cipherRef, SSLContext *ctx)
241 {
242     DESState *s = (DESState *) cipherRef;
243     void *subCipherRef = NULL;
244     int      rsaErr;
245     unsigned int  outputLen;
246     SSLBuffer     temp;
247     SSLERR        err;
248
249     if(cipherRef == NULL)
250         return SSLUnknownErr;
251
252     if(iv != NULL)
253     {
254         if((rsaErr = B_SetAlgorithmInfo(s->des, AI_DES_CBC_IV8,
255                                         (POINTER) iv->data)) !=
256            SSLNoErr)
257             return err;
258     }
259     else
260     {
261         if((rsaErr = B_SetAlgorithmInfo(s->des, AI_DES_CBC_IV8, s->iv)) != SSLNoErr)
262             return err;
263     }
264
265     ASSERT(src.length == dest.length);
266     ASSERT(src.length % 8 == 0);
267
268     if (src.data == dest.data)
269     /* BSAFE won't let you encrypt in place */
270     {
271         if (ERR(err = SSLAllocBuffer(&temp, src.length, &ctx->sysCtx)) != 0)
272             return err;
273         memcpy(temp.data, src.data, (size_t) src.length);
274     }
```

```
273     else
274         temp = src;
275
276     if ((rsaErr = B_EncryptUpdate(s->des, dest.data, &outputLen,
277         (unsigned int) dest.length, temp.data,
278         (unsigned int) temp.length,
279         (B_ALGORITHM_OBJ) 0, &ctx->sysCtx.yield)) != 0)
280     {
281         if (src.data == dest.data)
282             SSLFreeBuffer(&temp, &ctx->sysCtx);
283         return SSLUnknownErr;
284     }
285     ASSERT(outputLen == src.length);
286
287     if (src.data == dest.data)
288         SSLFreeBuffer(&temp, &ctx->sysCtx);
289
290     if (outputLen != src.length)
291         return SSLUnknownErr;
292
293     /* if not doing SSLoppy, save the IV for next time... */
294     if(iv == NULL)
295     {
296         unsigned char *buf;
297
298         if((rsaErr = B_GetAlgorithmInfo((POINTER *) &buf, s->des,
299             AI_DES_CBC_IV8))
300             != SSLNoErr)
301             return err;
302
303         memcpy(s->iv, buf, sizeof(s->iv));
304     }
305
306     /* memcpy(s->iv, dest.data + dest.length - 8, 8); */
307
308     return SSLNoErr;
309 }
310
311 SSLerr
312 SSLDESDecrypt(SSLBuffer src, SSLBuffer dest, SSLBuffer *iv, void *cipherRef, SSLContext *ctx)
313 {
314     DESState *s = (DESState *) cipherRef;
315     int         rsaErr;
316     unsigned int outputLen;
317     SSLBuffer    temp;
318     SSLerr       err;
319
320     if(cipherRef == NULL)
321         return SSLUnknownErr;
322
323     if(iv != NULL)
324     {
325         if((rsaErr = B_SetAlgorithmInfo(s->des, AI_DES_CBC_IV8, (POINTER) iv->data))
326             != SSLNoErr)
327             return err;
328     }
329     else
330     {
331         if((rsaErr = B_SetAlgorithmInfo(s->des, AI_DES_CBC_IV8, s->iv)) != SSLNoErr)
332             return err;
333     }
334
335     ASSERT(src.length == dest.length);
336     ASSERT(src.length % 8 == 0);
337
338     /* memcpy(s->iv, src.data + src.length - 8, 8); */
339
340     if (src.data == dest.data)
341     /* BSAFE won't let you encrypt in place */
342     {
343         if (ERR(err = SSLAllocBuffer(&temp, src.length, &ctx->sysCtx)) != 0)
344             return err;
```

```
344     memcpy(temp.data, src.data, (size_t) src.length);
345 }
346 else
347     temp = src;
348
349 if ((rsaErr = B_DecryptUpdate(s->des, dest.data, &outputLen,
350     (unsigned int) dest.length, temp.data,
351     (unsigned int) temp.length,
352     (B_ALGORITHM_OBJ) 0, &ctx->sysCtx.yield)) != 0)
353 {
354     if (src.data == dest.data)
355         SSLFreeBuffer(&temp, &ctx->sysCtx);
356     return SSLUnknownErr;
357 }
358
359 ASSERT(outputLen == src.length);
360
361 if (src.data == dest.data)
362     SSLFreeBuffer(&temp, &ctx->sysCtx);
363
364 if (outputLen != src.length)
365     return SSLUnknownErr;
366
367 /* if not doing SSLOppy, save the IV for next time... */
368 if(iv == NULL)
369 {
370     unsigned char *buf;
371     if((rsaErr = B_GetAlgorithmInfo((POINTER *) &buf, s->des,
372         AI_DES_CBC_IV8))
373         != SSLNoErr)
374         return err;
375     memcpy(s->iv, buf, sizeof(s->iv));
376 }
377
378 return SSLNoErr;
379 )
380
381 SSLerr
382 SSLDESfinish(void *cipherRef, SSLContext *ctx)
383 {
384     DESState *s = (DESState *) cipherRef;
385     SSLBuffer    desState;
386     SSLerr        err;
387
388     if(cipherRef == NULL)
389         return SSLUnknownErr;
390
391     B_DestroyAlgorithmObject(&(s->des));
392
393     memset(cipherRef, 0, sizeof(DESState));
394     desState.data = (unsigned char*)cipherRef;
395     desState.length = sizeof(DESState);
396
397     err = SSLFreeBuffer(&desState, &ctx->sysCtx);
398     return err;
399 }
400
401 SSLerr SSLDESExport(void *cipherRef, SSLContext *ctx, SSLBuffer *blob)
402 {
403     DESState *s = (DESState *) cipherRef;
404
405     if(cipherRef == NULL)
406         return SSLUnknownErr;
407
408     if(blob->length < (8 + 8))
409         return SSLMemoryErr;
410
411     memcpy(blob->data, s->key, 8);
412     memcpy(blob->data + 8, s->iv, 8);
413     /* memcpy(blob->data + 16, &(s->reading), sizeof(int)); */
414     blob->length = 16;
```

```
415
416     return SSLNoErr;
417 )
418
419 SSLerr SSLDESImport(void **cipherRef, SSLContext *ctx, SSLBuffer *blob)
420 {
421     unsigned char *key, *iv;
422
423     if(blob == NULL)
424         return SSLUnknownErr;
425     if(blob->length < 16)
426         return SSLUnknownErr;
427
428     key = blob->data;
429     iv = blob->data + 8;
430
431     return SSLDESInit(key, iv, cipherRef, ctx);
432 }
433
434
435 SSLerr SSL3DESInit(uint8 *key, uint8* iv, void **cipherRef, SSLContext *ctx);
436 SSLerr SSL3DESEncrypt(SSLBuffer src, SSLBuffer dest, SSLBuffer *iv, void *cipherRef, SSLContext
    *ctx);
437 SSLerr SSL3DESDecrypt(SSLBuffer src, SSLBuffer dest, SSLBuffer *iv, void *cipherRef, SSLContext
    *ctx);
438 SSLerr SSL3DESFinish(void *cipherRef, SSLContext *ctx);
439 SSLerr SSL3DESExport(void *cipherRef, SSLContext *ctx, SSLBuffer *blob);
440 SSLerr SSL3DESImport(void **cipherRef, SSLContext *ctx, SSLBuffer *blob);
441
442 SSLSymmetricCipher SSLCipher3DES_CBC = {
443     24,      /* Key size in bytes */
444     24,      /* Secret key size = 192 bits */
445     8,       /* IV size */
446     8,       /* Block size */
447     SSL3DESInit,
448     SSL3DESEncrypt,
449     SSL3DESDecrypt,
450     SSL3DESFinish,
451     SSL3DESExport,
452     SSL3DESImport
453 };
454
455 SSLerr
456 SSL3DESInit(uint8 *key, uint8* iv, void **cipherRef, SSLContext *ctx)
457 {
458     SSLBuffer          desState;
459     DESState *s;
460     static B_ALGORITHM_METHOD *chooser[] = { &AM_DES_EDE3_CBC_ENCRYPT,
461
462         &AM_DES_EDE3_CBC_DECRYPT, 0 };
463     B_KEY_OBJ          desKey;
464     ITEM               keyData;
465     SSLerr             err;
466     int                rsaErr;
467
468     if ((err = SSLAllocBuffer(&desState, sizeof(DESState), &ctx->sysCtx)) != 0)
469         return err;
470     s = (DESState *)desState.data;
471     if ((rsaErr = B_CreateAlgorithmObject(&(s->des))) != 0)
472         return SSLUnknownErr;
473     if ((rsaErr = B_SetAlgorithmInfo(s->des, AI_DES_EDE3_CBC_IV8, iv)) != 0)
474         return SSLUnknownErr;
475     memcpy(s->iv, iv, 8);
476
477     if ((rsaErr = B_CreateKeyObject(&desKey)) != 0)
478         return SSLUnknownErr;
479     keyData.data = key;
480     keyData.len = 24;
481     if ((rsaErr = B_SetKeyInfo(desKey, KI_24Byte, key)) != 0)
482     {
483         B_DestroyKeyObject(&desKey);
484     }
```



```
483         return SSLUnknownErr;
484     }
485     memcpy(s->key, key, 24);
486
487     if (cipherRef == (void*)&(ctx->writePending.symCipherState))
488     {
489         if ((rsaErr = B_EncryptInit(s->des, desKey, chooser,
490                                     &ctx->sysCtx.yield)) != 0)
491         {
492             B_DestroyKeyObject(&desKey);
493             return SSLUnknownErr;
494         }
495     }
496     else if (cipherRef == (void*)&(ctx->readPending.symCipherState))
497     {
498         if ((rsaErr = B_DecryptInit(s->des, desKey, chooser,
499                                     &ctx->sysCtx.yield)) != 0)
500         {
501             B_DestroyKeyObject(&desKey);
502             return SSLUnknownErr;
503         }
504     }
505     else
506         ASSERTMSG("Couldn't determine read/writeness");
507
508     B_DestroyKeyObject(&desKey);
509     *cipherRef = (void*)desState.data;
510     return SSLNoErr;
511 }
512
513 SSLERR
514 SSL3DESEncrypt(SSLBuffer src, SSLBuffer dest, SSLBuffer *iv, void *cipherRef, SSLContext *ctx)
515 {
516     DESState *s = (DESState *) cipherRef;
517     int      rsaErr;
518     unsigned int  outputLen;
519     SSLBuffer    temp;
520     SSLERR      err;
521
522     ASSERT(src.length == dest.length);
523     ASSERT(src.length % 8 == 0);
524     if(cipherRef == NULL)
525         return SSLUnknownErr;
526
527     if(iv != NULL)
528     {
529         if((rsaErr = B_SetAlgorithmInfo(s->des, AI_DES_EDE3_CBC_IV8,
530                                         (POINTER) iv->data)) !=
531            SSLNoErr)
532             return err;
533     }
534     else
535     {
536         if((rsaErr = B_SetAlgorithmInfo(s->des, AI_DES_EDE3_CBC_IV8, s->iv)) != SSLNoErr)
537             return err;
538     }
539
540     if (src.data == dest.data)
541     /* BSAFE won't let you encrypt in place */
542     {
543         if (ERR(err = SSLAllocBuffer(&temp, src.length, &ctx->sysCtx)) != 0)
544             return err;
545         memcpy(temp.data, src.data, (size_t) src.length);
546     }
547     else
548         temp = src;
549
550     if ((rsaErr = B_EncryptUpdate(s->des, dest.data, &outputLen,
551                                   (unsigned int) dest.length, temp.data,
552                                   (unsigned int) temp.length,
553                                   (B_ALGORITHM_OBJ) 0, &ctx->sysCtx.yield)) != 0)
```

```
553     ( if (src.data == dest.data)
554         SSLFreeBuffer(&temp, &ctx->sysCtx);
555         return SSLUnknownErr;
556     )
557
558     ASSERT(outputLen == src.length);
559
560     if (src.data == dest.data)
561         SSLFreeBuffer(&temp, &ctx->sysCtx);
562
563     if (outputLen != src.length)
564         return SSLUnknownErr;
565
566     if(iv == NULL)
567     {
568         unsigned char *buf;
569
570         if((rsaErr = B_GetAlgorithmInfo((POINTER *) &buf, s->des,
571             AI_DES_EDE3_CBC_IV8))
572             != SSLNoErr)
573             return err;
574         memcpy(s->iv, buf, sizeof(s->iv));
575     }
576
577     /* memcpy(s->iv, dest.data + dest.length - 8, 8); */
578
579     return SSLNoErr;
580 }
581
582 SSLErr
583 SSL3DESDecrypt(SSLBuffer src, SSLBuffer dest, SSLBuffer *iv, void *cipherRef, SSLContext *ctx)
584 {
585     DESState *s = (DESState *) cipherRef;
586     int      rsaErr;
587     unsigned int      outputLen;
588     SSLBuffer      temp;
589     SSLErr      err;
590
591     ASSERT(src.length == dest.length);
592     ASSERT(src.length % 8 == 0);
593     if(cipherRef == NULL)
594         return SSLNoErr;
595
596     if(iv != NULL)
597     {
598         if((rsaErr = B_SetAlgorithmInfo(s->des, AI_DES_EDE3_CBC_IV8,
599             (POINTER) iv->data)) !=
600             SSLNoErr)
601             return err;
602     }
603     else
604     {
605         if((rsaErr = B_SetAlgorithmInfo(s->des, AI_DES_EDE3_CBC_IV8, s->iv)) != SSLNoErr)
606             return err;
607     }
608
609     /* memcpy(s->iv, src.data + src.length - 8, 8); */
610
611     if (src.data == dest.data)
612     /* BSAFE won't let you encrypt in place */
613     {
614         if (ERR(err = SSLAllocBuffer(&temp, src.length, &ctx->sysCtx)) != 0)
615             return err;
616         memcpy(temp.data, src.data, (size_t) src.length);
617     }
618     else
619         temp = src;
620
621     if ((rsaErr = B_DecryptUpdate(s->des, dest.data, &outputLen,
622         (unsigned int) dest.length, temp.data,
623         (unsigned int) temp.length,
624         (B_ALGORITHM_OBJ) 0, &ctx->sysCtx.yield)) != 0)
```

```
623     { if (src.data == dest.data)
624         SSLFreeBuffer(&temp, &ctx->sysCtx);
625         return SSLUnknownErr;
626     }
627
628     if(iv == NULL)
629     {
630         unsigned char *buf;
631
632         if((rsaErr = B_GetAlgorithmInfo((POINTER *) &buf, s->des,
633             AI_DES_EDE3_CBC_IV8)) !=
        SSLNoErr)
634             return err;
635         memcpy(s->iv, buf, sizeof(s->iv));
636     }
637
638     ASSERT(outputLen == src.length);
639
640     if (src.data == dest.data)
641         SSLFreeBuffer(&temp, &ctx->sysCtx);
642
643     if (outputLen != src.length)
644         return SSLUnknownErr;
645
646     return SSLNoErr;
647 }
648
649 SSLerr
650 SSL3DESFinish(void *cipherRef, SSLContext *ctx)
651 {
652     DESState *s = (DESState *) cipherRef;
653     SSLBuffer    desState;
654     SSLerr      err;
655
656     if(cipherRef == NULL)
657         return SSLUnknownErr;
658
659     B_DestroyAlgorithmObject(&(s->des));
660
661     memset(cipherRef, 0, sizeof(DESState));
662     desState.data = (unsigned char *)cipherRef;
663     desState.length = sizeof(DESState);
664     err = SSLFreeBuffer(&desState, &ctx->sysCtx);
665     return err;
666 }
667
668 SSLerr SSL3DESExport(void *cipherRef, SSLContext *ctx, SSLBuffer *blob)
669 {
670     DESState *s = (DESState *) cipherRef;
671
672     if(cipherRef == NULL)
673         return SSLUnknownErr;
674
675     if(blob->length < (24 + 8))
676         return SSLMemoryErr;
677
678     memcpy(blob->data, s->key, 24);
679     memcpy(blob->data + 24, s->iv, 8);
680     blob->length = 32;
681
682     return SSLNoErr;
683 }
684
685 SSLerr SSL3DESImport(void **cipherRef, SSLContext *ctx, SSLBuffer *blob)
686 {
687     unsigned char *key, *iv;
688
689     if(blob == NULL)
690         return SSLUnknownErr;
691     if(blob->length < 32)
692         return SSLUnknownErr;
```

```
693
694     key = blob->data;
695     iv = blob->data + 24;
696
697     return SSL3DESInit(key, iv, cipherRef, ctx);
698 }
```